

All Food Equipment – Coffee Machine Purchasing Guide

Installation Checklist prior to buying your new espresso coffee machine

1. Enough bench space

Minimum depth 550 mm

Width vary (1 Group unit 490mm), (2 Group unit 680mm), (3 Group unit 910mm)

N.B. We suggest an additional 30 cm of space be allowed at front and sides of machine for a comfortable work area.

2. Holes as required drilled through bench or wall.

Minimum 1 3/4 inches (or 45mm) to clear.

3. Power point (240V 10amp or 15amp depending on unit) within 1 metre of machine.

4. Cold water 1/2 inch male stop cock fitted within 1 metre of machine.

5. Water connected / power connected. Our installation fee includes commissioning machine. This is not possible without water or power.

(Please indicate on purchase should you require this service)

Recommended Water Line by Plumber:

- 350 KPA Pressure Limiting Valve be fitted in line by your plumber with a half inch male fitting left to connect to.
- Heavy Duty water filter or water softener for areas that may have hard water (mostly country)

Installation Extra's includes:

- Connection to water and power
- Commissioning of the machine
- Demonstration of the use of the machine
- Operator maintenance demonstration
- Explanation of workings of the machine, which might make the difference between the machine working and not working when you need it most.
(This can be arranged by our office on purchase of the coffee machine)

Other Equipment needs

e.g. Coffee Bean Grinder, Milk Frothing Jugs, Milk Thermometers, Knock tube etc